DATASHEET

3M DBI SALA EXOFIT XE50 POSITIONING HARNESS SIZE 2



3M[™] DBI-SALA® ExoFit[™] XE50 Positioning Safety Harness with pass-through buckles.

The 3M[™] DBI-SALA® ExoFit[™] XE50 is designed with high-quality components specially developed for enhanced safety and fit while working at heights. Built with durable 26kN polyester webbing and alloy steel hardware, 3M[™] DBI-SALA® ExoFit[™]

Built with durable 26kN polyester webbing and alloy steel hardware, 3M ™ DBI-SALA® ExoFit ™ XE50 was created to endure the daily conditions of your job site.

• Cross Chest Buckle assembly for central front fall arrest attachment point - optimised position on body.

• Revolving torso adjusters (patented) for quick and easy harness fit and adjustment.

• Rear Large D-Ring, Front Standard D-Ring, Work Positioning Large Cranked D-Ring attachment points.

• Waist Padding - Optional comfort padding is available as accessory (order separately). Optional shoulder pads have yoke design to reduce uncomfortable chaffing to the neck.

• Integrated pSRL tunnel lets you quickly and easily connect and disconnect personal SRLs.

- Suspension trauma relief straps with low-profile design included.
- Steel hardware.

Product Code 3M1112706

Available in Colours

3M1112706

• Equipped with auto-resetting and re-positionable lanyard keepers for fast and easy parking of snap hooks and carabiners.

• 3M[™] Connected Safety ID (RFID) integrated for simplified inventory, inspection, and record management.

Industry: Construction, General Industrial, General Manufacturing, Transportation Max Weight: 140 kg

EN358:2019 CE EN361

ЗМ



