



BEESWIFT[®]
FOCUSED ON SAFETY

Product Code

CARC925SYNL



Anti Static



Arc Flash Protection



Cat 3 - High Risk



Fire Retardant



Hi Visibility



Protection for Welding and Allied Processes

DATASHEET

TWO TONE ARC WOVEN JACKET LGE



- Fire Retardant, Hi Vis, Anti-static, ARC Flash Jacket.
- 300gsm 60/40 Modacrylic/cotton blend.
- Triple stitch construction.
- 2 Lower pockets.
- Large qualifying icons on left arm.

- EN ISO 13688:2013 - General requirements for protective clothing
- EN ISO 20471:2013 Class 3 - Test method for high visibility
- EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
- EN 1149-5:2008 - Anti Static - Material performance and design requirements
- EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
- EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements

EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing

EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm²) - Open Arc testing

